

Luminaire

Code AD21304
Name PICTO LED HIGH FLUX NEWTK 4000K SPOT ND/AD NERO

Measurem.

Code FTS1800126
Name PICTO LED HIGH FLUX NEWTK 4000K SPOT ND/AD NERO

Luminaire Flux	6066.68 lm	Luminaire Power	65.00 W	Efficacy	93.33 lm/W	Efficiency	100.00%
Sources Flux	6066.68 lm	Maximum value	6529.51 cd/klm	Position	C=0.00 G=3.00	CG	Rotosymmetrical
Round Luminaire		Diam.	126 mm	Height	135 mm		
Round Luminous Area		Diam.	100 mm	Height	0 mm		
Horizontal Luminous Area		0.007854 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.001900 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-01-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		6066.68 lm	
LED Flux=8041lm LED Power=60W Eff=75% EfcLed=133lm/W EfcLum=93lm/W CCT=4000K Ra=90 SDCM=2 L70(6K)=50000h							
C.I.E.	94 96 99 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		


Diam=126mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %



Luminaire

Code AD21304
Name PICTO LED HIGH FLUX NEWTK 4000K SPOT ND/AD NERO

Measurem.


Code FTS1800126
Name PICTO LED HIGH FLUX NEWTK 4000K SPOT ND/AD NERO

Luminaire Flux	6066.68 lm	Luminaire Power	65.00 W	Efficacy	93.33 lm/W	Efficiency	100.00%
Sources Flux	6066.68 lm	Maximum value	6529.51 cd/klm	Position	C=0.00 G=3.00	CG	Rotosymmetrical
Round Luminaire		Diam.	126 mm	Height	135 mm		
Round Luminous Area		Diam.	100 mm	Height	0 mm		
Horizontal Luminous Area		0.007854 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.001900 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-01-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		6066.68 lm	
LED Flux=8041lm LED Power=60W Eff=75% EfcLed=133lm/W EfcLum=93lm/W CCT=4000K Ra=90 SDCM=2 L70(6K)=50000h							
C.I.E.	94 96 99 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.15	0.30	0.45	0.60	0.75	OC	0.15	0.30	0.45	0.60	0.75
OB	0.15	0.30	0.45	0.60	0.75	OD	0.15	0.30	0.45	0.60	0.75

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	38681.19	37319.61	4885.03	2463.56	405.90	129.42	101.73	103.13	76.56	26.31
OB	38681.19	37319.61	4885.03	2463.56	405.90	129.42	101.73	103.13	76.56	26.31
OC	38681.19	37319.61	4885.03	2463.56	405.90	129.42	101.73	103.13	76.56	26.31
OD	38681.19	37319.61	4885.03	2463.56	405.90	129.42	101.73	103.13	76.56	26.31



H[m]	D[m]	Max lux	Med lux	Alpha=8.5°+8.5°	G=0.0 Max non a G
1.00	0.30	39450	27659		
2.00	0.60	9862	6915		
3.00	0.90	4383	3073		
4.00	1.20	2466	1729		
5.00	1.50	1578	1106		