

Luminaire

Code AD21404
Name PICTO LED HIGH FLUX NEWTK 4000K WIDE FLOOD ND/AD NERO

Measurem.

Code FTS1800129
Name PICTO LED HIGH FLUX NEWTK 4000K WIDE FLOOD ND/AD NERO

Luminaire Flux	6043.36 lm	Luminaire Power	65.00 W	Efficacy	92.97 lm/W	Efficiency	100.00%
Sources Flux	6043.36 lm	Maximum value	1941.09 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	126 mm	Height	135 mm		
Round Luminous Area		Diam.	100 mm	Height	0 mm		
Horizontal Luminous Area		0.007854 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.001900 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		18-01-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		6043.36 lm	
LED Flux=8041lm LED Power=60W Eff=75% EfcLed=133lm/W EfcLum=93lm/W CCT=4000K Ra=90 SDCM=2 L70(6K)=50000h							
C.I.E.	92 96 99 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		

Diam=126mm




Semipiani C

180.0 ——— 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code AD21404
Name PICTO LED HIGH FLUX NEWTK 4000K WIDE FLOOD ND/AD NERO

Measurem.


Code FTS1800129
Name PICTO LED HIGH FLUX NEWTK 4000K WIDE FLOOD ND/AD NERO

Luminaire Flux	6043.36 lm	Luminaire Power	65.00 W	Efficacy	92.97 lm/W	Efficiency	100.00%
Sources Flux	6043.36 lm	Maximum value	1941.09 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	126 mm	Height	135 mm		
Round Luminous Area		Diam.	100 mm	Height	0 mm		
Horizontal Luminous Area		0.007854 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.001900 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		18-01-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		6043.36 lm	
LED Flux=8041lm LED Power=60W Eff=75% EfcLed=133lm/W EfcLum=93lm/W CCT=4000K Ra=90 SDCM=2 L70(6K)=50000h							
C.I.E.	92 96 99 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.35	0.71	1.06	1.42	1.77	OC	0.35	0.71	1.06	1.42	1.77
OB	0.35	0.71	1.06	1.42	1.77	OD	0.35	0.71	1.06	1.42	1.77

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	11730.69	11280.70	8079.80	3812.94	679.48	197.97	139.53	111.64	85.96	30.47
OB	11730.69	11280.70	8079.80	3812.94	679.48	197.97	139.53	111.64	85.96	30.47
OC	11730.69	11280.70	8079.80	3812.94	679.48	197.97	139.53	111.64	85.96	30.47
OD	11730.69	11280.70	8079.80	3812.94	679.48	197.97	139.53	111.64	85.96	30.47



H[m]	D[m]	Max lux	Med lux	Alpha=19.5°+19.5°	G=0.0
1.00	0.71	11731	7005		
2.00	1.42	2933	1751		
3.00	2.12	1303	778		
4.00	2.83	733	438		
5.00	3.54	469	280		