**Luminaire**
Code 2100010A
Name AoL SYSTEM S LIN.60 MAST.TERM. 3000K
**Measurem.**
Code FTS1902516
Name AoL SYSTEM S LIN.60 MAST.TERM. 3000K


| | | | | | | | |
|---|---|---|---|---|---|---|---|
| Luminaire Flux | 977.18 lm | Luminaire Power | 11.00 W | Efficacy | 88.83 lm/W | Efficiency | 100.00% |
| Sources Flux | 977.18 lm | Maximum value | 156.12 cd/klm | Position | C=5.00 G=5.00 | CG | Double Symmetrical |

| | | | | | |
|---|---|---|---|---|---|
| Rectangular Luminaire | Length | 580 mm | Width | 50 mm | Height | 50 mm |
| Rectangular Luminous Area | Length | 580 mm | Width | 50 mm | Height | 49 mm |
| Horizontal Luminous Area | 0.029000 m2 | | Emitting area on Plane 180° | | 0.029000 m2 | |
| Emitting area on Plane 0° | 0.029000 m2 | | Emitting area on Plane 270° | | 0.002500 m2 | |
| Emitting area on Plane 90° | 0.002500 m2 | | Glare area at 76° | | 0.035154 m2 | |
| Coordinate system | CG | | Symmetry Type | | Double Symmetrical | |
| Date | 05-09-2019 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | 0.00 | | Measurement Flux | | 977.18 lm | |

LED Flux=1225lm LED Power=11W Eff=80% EfcLed=111lm/W EfcLum=89lm/W CCT=3000K Ra=80 SDCM=3 L70(6K)=50000h


| | | | |
|---|---|---|---|
| C.I.E. | 33 60 82 69 100 | D DIN 5040 | B21 |
| F UTE | 0.69 H + 0.31 T | B NBN | BZ 6 |

580mm x 50mm




Semipiani C

180.0 — 0.0
270.0 — 90.0




ULOR 31.35 %
DLOR 68.65 %
RN 31.35 %

**Luminaire**
Code 2100010A
Name AoL SYSTEM S LIN.60 MAST.TERM. 3000K
**Measurem.**
Code FTS1902516
Name AoL SYSTEM S LIN.60 MAST.TERM. 3000K

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| Luminaire Flux | 977.18 lm | Luminaire Power | 11.00 W | Efficacy | 88.83 lm/W | Efficiency | 100.00% |
| Sources Flux | 977.18 lm | Maximum value | 156.12 cd/klm | Position | C=5.00 G=5.00 | CG | Double Symmetrical |

| | | | | | |
|---|---|---|---|---|---|
| Rectangular Luminaire | Length | 580 mm | Width | 50 mm | Height | 50 mm |
| Rectangular Luminous Area | Length | 580 mm | Width | 50 mm | Height | 49 mm |

| | | | |
|---|---|---|---|
| Horizontal Luminous Area | 0.029000 m2 | Emitting area on Plane 180° | 0.029000 m2 |
| Emitting area on Plane 0° | 0.029000 m2 | Emitting area on Plane 270° | 0.002500 m2 |
| Emitting area on Plane 90° | 0.002500 m2 | Glare area at 76° | 0.035154 m2 |

| | | | |
|---|---|---|---|
| Coordinate system | CG | Symmetry Type | Double Symmetrical |
| Date | 05-09-2019 | Maximum Gamma Angle | 180 |
| Measurement Distance | 0.00 | Measurement Flux | 977.18 lm |

LED Flux=1225lm LED Power=11W Eff=80% EfcLed=111lm/W EfcLum=89lm/W CCT=3000K Ra=80 SDCM=3 L70(6K)=50000h

| | | | |
|---|---|---|---|
| C.I.E. | 33 60 82 69 100 | D DIN 5040 | B21 |
| F UTE | 0.69 H + 0.31 T | B NBN | BZ 6 |

Apertura a destra non trovata, gamma =8

Apertura a destra non trovata, gamma =8

Apertura a destra non trovata, gamma =8