Luminaire
Code 2107010A
Name AoL SYSTEM S LIN.120 SLAVE INTERM 3000K
Measurem.
Code FTS1902526
Name AoL SYSTEM S LIN.120 SLAVE INTERM 3000K


Luminaire Flux	1954.36 lm	Luminaire Power	21.00 W	Efficacy	93.06 lm/W	Efficiency	100.00%
Sources Flux	1954.36 lm	Maximum value	156.12 cd/klm	Position	C=5.00 G=5.00	CG	Double Symmetrical

Rectangular Luminaire		Length	1200 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area		Length	1200 mm	Width	50 mm	Height	50 mm
Horizontal Luminous Area		0.060000 m2		Emitting area on Plane 180°		0.060000 m2	
Emitting area on Plane 0°		0.060000 m2		Emitting area on Plane 270°		0.002500 m2	
Emitting area on Plane 90°		0.002500 m2		Glare area at 76°		0.072733 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		05-09-2019		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1954.36 lm	

LED Flux=2450lm LED Power=21W Eff=80% EfcLed=117lm/W EfcLum=93lm/W CCT=3000K Ra=80 SDCM=3 L70(6K)=50000h


C.I.E.	33 60 82 69 100	D DIN 5040	B21
F UTE	0.69 H + 0.31 T	B NBN	BZ 6

1200mm x 50mm



Semipiani C

180.0 — 0.0
270.0 — 90.0



ULOR 31.35 %
DLOR 68.65 %
RN 31.35 %

Luminaire
Code 2107010A
Name AoL SYSTEM S LIN.120 SLAVE INTERM 3000K
Measurem.
Code FTS1902526
Name AoL SYSTEM S LIN.120 SLAVE INTERM 3000K

Luminaire Flux	1954.36 lm	Luminaire Power	21.00 W	Efficacy	93.06 lm/W	Efficiency	100.00%
Sources Flux	1954.36 lm	Maximum value	156.12 cd/klm	Position	C=5.00 G=5.00	CG	Double Symmetrical

Rectangular Luminaire	Length	1200 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area	Length	1200 mm	Width	50 mm	Height	50 mm
Horizontal Luminous Area	0.060000 m2		Emitting area on Plane 180°		0.060000 m2	
Emitting area on Plane 0°	0.060000 m2		Emitting area on Plane 270°		0.002500 m2	
Emitting area on Plane 90°	0.002500 m2		Glare area at 76°		0.072733 m2	
Coordinate system	CG		Symmetry Type		Double Symmetrical	
Date	05-09-2019		Maximum Gamma Angle		180	
Measurement Distance	0.00		Measurement Flux		1954.36 lm	

LED Flux=2450lm LED Power=21W Eff=80% EfcLed=117lm/W EfcLum=93lm/W CCT=3000K Ra=80 SDCM=3 L70(6K)=50000h

C.I.E.	33 60 82 69 100	D DIN 5040	B21
F UTE	0.69 H + 0.31 T	B NBN	BZ 6

Apertura a destra non trovata, gamma =8

Apertura a destra non trovata, gamma =8

Apertura a destra non trovata, gamma =8