
Luminaire
Code 2110010A
Name AoL SYSTEM S LIN.180 SLAVE TERM. 3000K
Measurem.
Code FTS1902535
Name AoL SYSTEM S LIN.180 SLAVE TERM. 3000K

Luminaire Flux	2931.54 lm	Luminaire Power	33.00 W	Efficacy	88.83 lm/W	Efficiency	100.00%
Sources Flux	2931.54 lm	Maximum value	156.12 cd/klm	Position	C=5.00 G=5.00	CG	Double Symmetrical


Rectangular Luminaire		Length	1800 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area		Length	1800 mm	Width	50 mm	Height	50 mm
Horizontal Luminous Area		0.090000 m2		Emitting area on Plane 180°		0.090000 m2	
Emitting area on Plane 0°		0.090000 m2		Emitting area on Plane 270°		0.002500 m2	
Emitting area on Plane 90°		0.002500 m2		Glare area at 76°		0.109100 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		05-09-2019		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2931.54 lm	

LED Flux=3675lm LED Power=33W Eff=80% EfcLed=111lm/W EfcLum=89lm/W CCT=3000K Ra=80 SDCM=3 L70(6K)=50000h

C.I.E.	33 60 82 69 100	D DIN 5040	B21
F UTE	0.69 H + 0.31 T	B NBN	BZ 6



1800mm x 50mm



Semipiani C

180.0 0.0
270.0 90.0

ULOR 31.35 %
DLOR 68.65 %
RN 31.35 %

Luminaire
Code 2110010A
Name AoL SYSTEM S LIN.180 SLAVE TERM. 3000K
Measurem.
Code FTS1902535
Name AoL SYSTEM S LIN.180 SLAVE TERM. 3000K

Luminaire Flux	2931.54 lm	Luminaire Power	33.00 W	Efficacy	88.83 lm/W	Efficiency	100.00%
Sources Flux	2931.54 lm	Maximum value	156.12 cd/klm	Position	C=5.00 G=5.00	CG	Double Symmetrical

Rectangular Luminaire		Length	1800 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area		Length	1800 mm	Width	50 mm	Height	50 mm
Horizontal Luminous Area		0.090000 m2		Emitting area on Plane 180°		0.090000 m2	
Emitting area on Plane 0°		0.090000 m2		Emitting area on Plane 270°		0.002500 m2	
Emitting area on Plane 90°		0.002500 m2		Glare area at 76°		0.109100 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		05-09-2019		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2931.54 lm	

LED Flux=3675lm LED Power=33W Eff=80% EfcLed=111lm/W EfcLum=89lm/W CCT=3000K Ra=80 SDCM=3 L70(6K)=50000h

C.I.E.	33 60 82 69 100	D DIN 5040	B21
F UTE	0.69 H + 0.31 T	B NBN	BZ 6

Apertura a destra non trovata, gamma =8

Apertura a destra non trovata, gamma =8

Apertura a destra non trovata, gamma =8