Luminaire
Code 2116C10A
Name AoL SYSTEM S 45° SLAVE TERM. DX 3500K
Measurem.
Code FTS1902606
Name AoL SYSTEM S 45° SLAVE TERM. DX 3500K

Luminaire Flux	979.28 lm	Luminaire Power	11.00 W	Efficacy	89.03 lm/W	Efficiency	100.00%
Sources Flux	979.28 lm	Maximum value	160.44 cd/klm	Position	C=0.00 G=8.00	CG	Sym. on planes 0-180


Rectangular Luminaire	Length	590 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area	Length	590 mm	Width	50 mm	Height	50 mm

Horizontal Luminous Area	0.029500 m2	Emitting area on Plane 180°	0.029500 m2
Emitting area on Plane 0°	0.029500 m2	Emitting area on Plane 270°	0.002500 m2
Emitting area on Plane 90°	0.002500 m2	Glare area at 76°	0.035760 m2


Coordinate system	CG	Symmetry Type	Sym. on planes 0-180
Date	16-05-2019	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	979.28 lm

LED Flux=1244lm LED Power=11W Eff=79% EfcLed=113lm/W EfcLum=89lm/W CCT=3500K Ra=80 SDCM=3 L70(6K)=50000h

C.I.E.	33 61 83 70 100	D DIN 5040	B21
F UTE	0.70 H + 0.30 T	B NBN	BZ 6



590mm x 50mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 30.46 %
DLOR 69.54 %
RN 30.46 %

Luminaire
Code 2116C10A
Name AoL SYSTEM S 45° SLAVE TERM. DX 3500K
Measurem.
Code FTS1902606
Name AoL SYSTEM S 45° SLAVE TERM. DX 3500K

Luminaire Flux	979.28 lm	Luminaire Power	11.00 W	Efficacy	89.03 lm/W	Efficiency	100.00%
Sources Flux	979.28 lm	Maximum value	160.44 cd/klm	Position	C=0.00 G=8.00	CG	Sym. on planes 0-180

Rectangular Luminaire	Length	590 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area	Length	590 mm	Width	50 mm	Height	50 mm

Horizontal Luminous Area	0.029500 m2	Emitting area on Plane 180°	0.029500 m2
Emitting area on Plane 0°	0.029500 m2	Emitting area on Plane 270°	0.002500 m2
Emitting area on Plane 90°	0.002500 m2	Glare area at 76°	0.035760 m2

Coordinate system	CG	Symmetry Type	Sym. on planes 0-180
Date	16-05-2019	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	979.28 lm

LED Flux=1244lm LED Power=11W Eff=79% EfcLed=113lm/W EfcLum=89lm/W CCT=3500K Ra=80 SDCM=3 L70(6K)=50000h

C.I.E.	33 61 83 70 100	D DIN 5040	B21
F UTE	0.70 H + 0.30 T	B NBN	BZ 6

Apertura a destra non trovata, gamma =8

Apertura a destra non trovata, gamma =8

Apertura a destra non trovata, gamma =8