Luminaire
Code 2130010A
Name AoL SYSTEM C/W LIN.60 MAST.TERM. 3000K
Measurem.
Code FTS1902519
Name AoL SYSTEM C/W LIN.60 MAST.TERM. 3000K


Luminaire Flux	977.18 lm	Luminaire Power	11.00 W	Efficacy	88.83 lm/W	Efficiency	100.00%
Sources Flux	977.18 lm	Maximum value	156.12 cd/klm	Position	C=5.00 G=5.00	CG	Double Symmetrical

Rectangular Luminaire	Length	580 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area	Length	580 mm	Width	50 mm	Height	49 mm
Horizontal Luminous Area	0.029000 m2		Emitting area on Plane 180°		0.029000 m2	
Emitting area on Plane 0°	0.029000 m2		Emitting area on Plane 270°		0.002500 m2	
Emitting area on Plane 90°	0.002500 m2		Glare area at 76°		0.035154 m2	


Coordinate system	CG	Symmetry Type	Double Symmetrical
Date	05-09-2019	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	977.18 lm

LED Flux=1225lm LED Power=11W Eff=80% EfcLed=111lm/W EfcLum=89lm/W CCT=3000K Ra=80 SDCM=3 L70(6K)=50000h

C.I.E.	33 60 82 69 100	D DIN 5040	B21
F UTE	0.69 H + 0.31 T	B NBN	BZ 6



580mm x 50mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 31.35 %
DLOR 68.65 %
RN 31.35 %

Luminaire
Code 2130010A
Name AoL SYSTEM C/W LIN.60 MAST.TERM. 3000K
Measurem.
Code FTS1902519
Name AoL SYSTEM C/W LIN.60 MAST.TERM. 3000K

Luminaire Flux	977.18 lm	Luminaire Power	11.00 W	Efficacy	88.83 lm/W	Efficiency	100.00%
Sources Flux	977.18 lm	Maximum value	156.12 cd/klm	Position	C=5.00 G=5.00	CG	Double Symmetrical

Rectangular Luminaire	Length	580 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area	Length	580 mm	Width	50 mm	Height	49 mm

Horizontal Luminous Area	0.029000 m2	Emitting area on Plane 180°	0.029000 m2
Emitting area on Plane 0°	0.029000 m2	Emitting area on Plane 270°	0.002500 m2
Emitting area on Plane 90°	0.002500 m2	Glare area at 76°	0.035154 m2

Coordinate system	CG	Symmetry Type	Double Symmetrical
Date	05-09-2019	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	977.18 lm

LED Flux=1225lm LED Power=11W Eff=80% EfcLed=111lm/W EfcLum=89lm/W CCT=3000K Ra=80 SDCM=3 L70(6K)=50000h

C.I.E.	33 60 82 69 100	D DIN 5040	B21
F UTE	0.69 H + 0.31 T	B NBN	BZ 6

Apertura a destra non trovata, gamma =8

Apertura a destra non trovata, gamma =8

Apertura a destra non trovata, gamma =8