
Luminaire
Code 2130C10A
Name AoL SYSTEM C/W LIN.60 MAST.TERM. 3500K
Measurem.
Code FTS1902578
Name AoL SYSTEM C/W LIN.60 MAST.TERM. 3500K

Luminaire Flux	992.34 lm	Luminaire Power	11.00 W	Efficacy	90.21 lm/W	Efficiency	100.00%
Sources Flux	992.34 lm	Maximum value	156.12 cd/klm	Position	C=5.00 G=5.00	CG	Double Symmetrical


Rectangular Luminaire	Length	580 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area	Length	580 mm	Width	50 mm	Height	49 mm
Horizontal Luminous Area	0.029000 m2		Emitting area on Plane 180°		0.029000 m2	
Emitting area on Plane 0°	0.029000 m2		Emitting area on Plane 270°		0.002500 m2	
Emitting area on Plane 90°	0.002500 m2		Glare area at 76°		0.035154 m2	
Coordinate system	CG		Symmetry Type		Double Symmetrical	
Date	05-09-2019		Maximum Gamma Angle		180	
Measurement Distance	0.00		Measurement Flux		992.34 lm	

LED Flux=1244lm LED Power=11W Eff=80% EfcLed=113lm/W EfcLum=90lm/W CCT=3500K Ra=80 SDCM=3 L70(6K)=50000h

C.I.E.	33 60 82 69 100	D DIN 5040	B21
F UTE	0.69 H + 0.31 T	B NBN	BZ 6



580mm x 50mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 31.35 %
DLOR 68.65 %
RN 31.35 %

Luminaire
Code 2130C10A
Name AoL SYSTEM C/W LIN.60 MAST.TERM. 3500K
Measurem.
Code FTS1902578
Name AoL SYSTEM C/W LIN.60 MAST.TERM. 3500K

Luminaire Flux	992.34 lm	Luminaire Power	11.00 W	Efficacy	90.21 lm/W	Efficiency	100.00%
Sources Flux	992.34 lm	Maximum value	156.12 cd/klm	Position	C=5.00 G=5.00	CG	Double Symmetrical

Rectangular Luminaire	Length	580 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area	Length	580 mm	Width	50 mm	Height	49 mm

Horizontal Luminous Area	0.029000 m2	Emitting area on Plane 180°	0.029000 m2
Emitting area on Plane 0°	0.029000 m2	Emitting area on Plane 270°	0.002500 m2
Emitting area on Plane 90°	0.002500 m2	Glare area at 76°	0.035154 m2

Coordinate system	CG	Symmetry Type	Double Symmetrical
Date	05-09-2019	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	992.34 lm

LED Flux=1244lm LED Power=11W Eff=80% EfcLed=113lm/W EfcLum=90lm/W CCT=3500K Ra=80 SDCM=3 L70(6K)=50000h

C.I.E.	33 60 82 69 100	D DIN 5040	B21
F UTE	0.69 H + 0.31 T	B NBN	BZ 6

Apertura a destra non trovata, gamma =8

Apertura a destra non trovata, gamma =8

Apertura a destra non trovata, gamma =8