
Luminaire
Code M263445
Name EVERYTHING 150 QUADRATO TRIM ORIENTABILE LED VERY WIDE FLOOD CORNICE NERO / DEFL. NERO 3000K
Measurem.
Code FTS1900970
Name EVERYTHING 150 QUADRATO TRIM ORIENTABILE LED VERY WIDE FLOOD CORNICE NERO / DEFL. NERO 3000K


Luminaire Flux	1677.14 lm	Luminaire Power	24.00 W	Efficacy	69.88 lm/W	Efficiency	100.00%
Sources Flux	1677.14 lm	Maximum value	1459.03 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Round Luminaire	Diam. 150 mm	Height	137 mm
Round Luminous Area	Diam. 120 mm	Height	0 mm
Horizontal Luminous Area	0.011310 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.002736 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	04-03-2015	Maximum Gamma Angle	90
Measurement Distance	0.00	Measurement Flux	1677.14 lm

LED Flux=2763lm LED Power=24W Eff=60,7% EfcLed=115lm/W EfcLum=70lm/W Ra=90 SDCM=3 L70(6K)=50000h

C.I.E.	96 100 100 100 100	D DIN 5040	A60
F UTE	1.00 A	B NBN	BZ 1





Semipiani C

180.0 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %

Luminaire
Code M263445
Name EVERYTHING 150 QUADRATO TRIM ORIENTABILE LED VERY WIDE FLOOD CORNICE NERO / DEFL. NERO 3000K
Measurem.
Code FTS1900970
Name EVERYTHING 150 QUADRATO TRIM ORIENTABILE LED VERY WIDE FLOOD CORNICE NERO / DEFL. NERO 3000K

Luminaire Flux	1677.14 lm	Luminaire Power	24.00 W	Efficacy	69.88 lm/W	Efficiency	100.00%
Sources Flux	1677.14 lm	Maximum value	1459.03 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Round Luminaire	Diam. 150 mm	Height	137 mm
Round Luminous Area	Diam. 120 mm	Height	0 mm
Horizontal Luminous Area	0.011310 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.002736 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	04-03-2015	Maximum Gamma Angle	90
Measurement Distance	0.00	Measurement Flux	1677.14 lm

LED Flux=2763lm LED Power=24W Eff=60,7% EfcLed=115lm/W EfcLum=70lm/W Ra=90 SDCM=3 L70(6K)=50000h


C.I.E.	96 100 100 100 100	D DIN 5040	A60
F UTE	1.00 A	B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.43	0.85	1.28	1.70	2.13	OC	0.43	0.85	1.28	1.70	2.13
OB	0.43	0.85	1.28	1.70	2.13	OD	0.43	0.85	1.28	1.70	2.13

Luminous Intensities [cd/klm]

	0	5	15	25	35	45	55	65	75	85
OA	2446.99	2364.18	1768.87	1130.82	557.42	94.79	6.12	0.55	0.26	0.08
OB	2446.99	2364.18	1768.87	1130.82	557.42	94.79	6.12	0.55	0.26	0.08
OC	2446.99	2364.18	1768.87	1130.82	557.42	94.79	6.12	0.55	0.26	0.08
OD	2446.99	2364.18	1768.87	1130.82	557.42	94.79	6.12	0.55	0.26	0.08



H[m]	D[m]	Max lux	Med lux	Alpha=23.1°+23.1° G=0.0
1.00	0.85	2447	1360	
2.00	1.70	612	340	
3.00	2.56	272	151	
4.00	3.41	153	85	
5.00	4.26	98	54	