Luminaire
Code 2162C10A
Name AoL SYSTEM SR LIN.120 MAST.INTERM 3500K
Measurem.
Code FTS1902591
Name AoL SYSTEM SR LIN.120 MAST.INTERM 3500K

Luminaire Flux	1984.67 lm	Luminaire Power	21.00 W	Efficacy	94.51 lm/W	Efficiency	100.00%
Sources Flux	1984.67 lm	Maximum value	156.12 cd/klm	Position	C=5.00 G=5.00	CG	Double Symmetrical


Rectangular Luminaire	Length	1200 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area	Length	1200 mm	Width	50 mm	Height	50 mm

Horizontal Luminous Area	0.060000 m2	Emitting area on Plane 180°	0.060000 m2
Emitting area on Plane 0°	0.060000 m2	Emitting area on Plane 270°	0.002500 m2
Emitting area on Plane 90°	0.002500 m2	Glare area at 76°	0.072733 m2


Coordinate system	CG	Symmetry Type	Double Symmetrical
Date	05-09-2019	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	1984.67 lm

LED Flux=2488lm LED Power=21W Eff=80% EfcLed=118lm/W EfcLum=95lm/W CCT=3500K Ra=80 SDCM=3 L70(6K)=50000h

C.I.E.	33 60 82 69 100	D DIN 5040	B21
F UTE	0.69 H + 0.31 T	B NBN	BZ 6



1200mm x 50mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 31.35 %
DLOR 68.65 %
RN 31.35 %

Luminaire
Code 2162C10A
Name AoL SYSTEM SR LIN.120 MAST.INTERM 3500K
Measurem.
Code FTS1902591
Name AoL SYSTEM SR LIN.120 MAST.INTERM 3500K

Luminaire Flux	1984.67 lm	Luminaire Power	21.00 W	Efficacy	94.51 lm/W	Efficiency	100.00%
Sources Flux	1984.67 lm	Maximum value	156.12 cd/klm	Position	C=5.00 G=5.00	CG	Double Symmetrical

Rectangular Luminaire		Length	1200 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area		Length	1200 mm	Width	50 mm	Height	50 mm
Horizontal Luminous Area		0.060000 m2		Emitting area on Plane 180°		0.060000 m2	
Emitting area on Plane 0°		0.060000 m2		Emitting area on Plane 270°		0.002500 m2	
Emitting area on Plane 90°		0.002500 m2		Glare area at 76°		0.072733 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		05-09-2019		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1984.67 lm	

LED Flux=2488lm LED Power=21W Eff=80% EfcLed=118lm/W EfcLum=95lm/W CCT=3500K Ra=80 SDCM=3 L70(6K)=50000h

C.I.E.	33 60 82 69 100	D DIN 5040	B21
F UTE	0.69 H + 0.31 T	B NBN	BZ 6

Apertura a destra non trovata, gamma =8

Apertura a destra non trovata, gamma =8

Apertura a destra non trovata, gamma =8