Luminaire
Code 2164010A
Name AoL SYSTEM SR LIN.180 MAST.INTERM 3000K
Measurem.
Code FTS1902542
Name AoL SYSTEM SR LIN.180 MAST.INTERM 3000K

Luminaire Flux	2931.54 lm	Luminaire Power	33.00 W	Efficacy	88.83 lm/W	Efficiency	100.00%
Sources Flux	2931.54 lm	Maximum value	156.12 cd/klm	Position	C=5.00 G=5.00	CG	Double Symmetrical

Rectangular Luminaire	Length	1800 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area	Length	1800 mm	Width	50 mm	Height	50 mm


Horizontal Luminous Area	0.090000 m2	Emitting area on Plane 180°	0.090000 m2
Emitting area on Plane 0°	0.090000 m2	Emitting area on Plane 270°	0.002500 m2
Emitting area on Plane 90°	0.002500 m2	Glare area at 76°	0.109100 m2

Coordinate system	CG	Symmetry Type	Double Symmetrical
Date	05-09-2019	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	2931.54 lm

LED Flux=3675lm LED Power=33W Eff=80% EfcLed=111lm/W EfcLum=89lm/W CCT=3000K Ra=80 SDCM=3 L70(6K)=50000h


C.I.E.	33 60 82 69 100	D DIN 5040	B21
F UTE	0.69 H + 0.31 T	B NBN	BZ 6

1800mm x 50mm



Semipiani C

180.0 — 0.0
270.0 — 90.0



ULOR 31.35 %
DLOR 68.65 %
RN 31.35 %

Luminaire
Code 2164010A
Name AoL SYSTEM SR LIN.180 MAST.INTERM 3000K
Measurem.
Code FTS1902542
Name AoL SYSTEM SR LIN.180 MAST.INTERM 3000K

Luminaire Flux	2931.54 lm	Luminaire Power	33.00 W	Efficacy	88.83 lm/W	Efficiency	100.00%
Sources Flux	2931.54 lm	Maximum value	156.12 cd/klm	Position	C=5.00 G=5.00	CG	Double Symmetrical

Rectangular Luminaire		Length	1800 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area		Length	1800 mm	Width	50 mm	Height	50 mm
Horizontal Luminous Area		0.090000 m2		Emitting area on Plane 180°		0.090000 m2	
Emitting area on Plane 0°		0.090000 m2		Emitting area on Plane 270°		0.002500 m2	
Emitting area on Plane 90°		0.002500 m2		Glare area at 76°		0.109100 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		05-09-2019		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2931.54 lm	

LED Flux=3675lm LED Power=33W Eff=80% EfcLed=111lm/W EfcLum=89lm/W CCT=3000K Ra=80 SDCM=3 L70(6K)=50000h

C.I.E.	33 60 82 69 100	D DIN 5040	B21
F UTE	0.69 H + 0.31 T	B NBN	BZ 6

Apertura a destra non trovata, gamma =8

Apertura a destra non trovata, gamma =8

Apertura a destra non trovata, gamma =8