Luminaire
Code 2169010A
Name AoL SYSTEM SR 60° MAST.TERM.DX 3000K
Measurem.
Code FTS1902571
Name AoL SYSTEM SR 60° MAST.TERM.DX 3000K


Luminaire Flux	690.61 lm	Luminaire Power	8.00 W	Efficacy	86.33 lm/W	Efficiency	100.00%
Sources Flux	690.61 lm	Maximum value	162.58 cd/klm	Position	C=20.00 G=5.00	CG	Sym. on planes 0-180

Rectangular Luminaire	Length	475 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area	Length	475 mm	Width	50 mm	Height	50 mm
Horizontal Luminous Area	0.023750 m2		Emitting area on Plane 180°		0.023750 m2	
Emitting area on Plane 0°	0.023750 m2		Emitting area on Plane 270°		0.002500 m2	
Emitting area on Plane 90°	0.002500 m2		Glare area at 76°		0.028790 m2	
Coordinate system	CG		Symmetry Type		Sym. on planes 0-180	
Date	17-05-2019		Maximum Gamma Angle		180	
Measurement Distance	0.00		Measurement Flux		690.61 lm	

LED Flux=903lm LED Power=8W Eff=76% EfcLed=113lm/W EfcLum=86lm/W CCT=3000K Ra=80 SDCM=3 L70(6K)=50000h


C.I.E.	33 61 83 70 100	D DIN 5040	B21
F UTE	0.70 H + 0.30 T	B NBN	BZ 6

475mm x 50mm



Semipiani C

180.0 — 0.0
270.0 — 90.0



ULOR 30.45 %
DLOR 69.55 %
RN 30.45 %

Luminaire
Code 2169010A
Name AoL SYSTEM SR 60° MAST.TERM.DX 3000K
Measurem.
Code FTS1902571
Name AoL SYSTEM SR 60° MAST.TERM.DX 3000K

Luminaire Flux	690.61 lm	Luminaire Power	8.00 W	Efficacy	86.33 lm/W	Efficiency	100.00%
Sources Flux	690.61 lm	Maximum value	162.58 cd/klm	Position	C=20.00 G=5.00	CG	Sym. on planes 0-180

Rectangular Luminaire	Length	475 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area	Length	475 mm	Width	50 mm	Height	50 mm
Horizontal Luminous Area	0.023750 m2		Emitting area on Plane 180°		0.023750 m2	
Emitting area on Plane 0°	0.023750 m2		Emitting area on Plane 270°		0.002500 m2	
Emitting area on Plane 90°	0.002500 m2		Glare area at 76°		0.028790 m2	
Coordinate system	CG		Symmetry Type		Sym. on planes 0-180	
Date	17-05-2019		Maximum Gamma Angle		180	
Measurement Distance	0.00		Measurement Flux		690.61 lm	

LED Flux=903lm LED Power=8W Eff=76% EfcLed=113lm/W EfcLum=86lm/W CCT=3000K Ra=80 SDCM=3 L70(6K)=50000h

C.I.E.	33 61 83 70 100	D DIN 5040	B21
F UTE	0.70 H + 0.30 T	B NBN	BZ 6

Apertura a destra non trovata, gamma =3

Apertura a destra non trovata, gamma =3

Apertura a destra non trovata, gamma =3