Luminaire
Code 2170C10A
Name AoL SYSTEM SR 60° MAST.INTERM.3500K
Measurem.
Code FTS1902631
Name AoL SYSTEM SR 60° MAST.INTERM.3500K


Luminaire Flux	701.32 lm	Luminaire Power	8.00 W	Efficacy	87.66 lm/W	Efficiency	100.00%
Sources Flux	701.32 lm	Maximum value	162.58 cd/klm	Position	C=20.00 G=5.00	CG	Sym. on planes 0-180

Rectangular Luminaire	Length	475 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area	Length	475 mm	Width	50 mm	Height	50 mm
Horizontal Luminous Area	0.023750 m2		Emitting area on Plane 180°		0.023750 m2	
Emitting area on Plane 0°	0.023750 m2		Emitting area on Plane 270°		0.002500 m2	
Emitting area on Plane 90°	0.002500 m2		Glare area at 76°		0.028790 m2	
Coordinate system	CG		Symmetry Type		Sym. on planes 0-180	
Date	17-05-2019		Maximum Gamma Angle		180	
Measurement Distance	0.00		Measurement Flux		701.32 lm	

LED Flux=917lm LED Power=8W Eff=76% EfcLed=115lm/W EfcLum=88lm/W CCT=3500K Ra=80 SDCM=3 L70(6K)=50000h


C.I.E.	33 61 83 70 100	D DIN 5040	B21
F UTE	0.70 H + 0.30 T	B NBN	BZ 6

475mm x 50mm



Semipiani C

180.0 — 0.0
270.0 — 90.0



ULOR 30.45 %
DLOR 69.55 %
RN 30.45 %

Luminaire
Code 2170C10A
Name AoL SYSTEM SR 60° MAST.INTERM.3500K
Measurem.
Code FTS1902631
Name AoL SYSTEM SR 60° MAST.INTERM.3500K

Luminaire Flux	701.32 lm	Luminaire Power	8.00 W	Efficacy	87.66 lm/W	Efficiency	100.00%
Sources Flux	701.32 lm	Maximum value	162.58 cd/klm	Position	C=20.00 G=5.00	CG	Sym. on planes 0-180

Rectangular Luminaire	Length	475 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area	Length	475 mm	Width	50 mm	Height	50 mm

Horizontal Luminous Area	0.023750 m2	Emitting area on Plane 180°	0.023750 m2
Emitting area on Plane 0°	0.023750 m2	Emitting area on Plane 270°	0.002500 m2
Emitting area on Plane 90°	0.002500 m2	Glare area at 76°	0.028790 m2

Coordinate system	CG	Symmetry Type	Sym. on planes 0-180
Date	17-05-2019	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	701.32 lm

LED Flux=917lm LED Power=8W Eff=76% EfcLed=115lm/W EfcLum=88lm/W CCT=3500K Ra=80 SDCM=3 L70(6K)=50000h

C.I.E.	33 61 83 70 100	D DIN 5040	B21
F UTE	0.70 H + 0.30 T	B NBN	BZ 6

Apertura a destra non trovata, gamma =3

Apertura a destra non trovata, gamma =3

Apertura a destra non trovata, gamma =3