
Luminaire
Code FU50201APP+AP91400
Name VECTOR 55 PENDANT FUNIVIA 927 WF BCO
Measurem.
Code FTS2001454-A
Name VECTOR 55 PENDANT FUNIVIA 927 WF BCO

Luminaire Flux	1231 lm	Luminaire Power	23.0 W	Efficacy	53.527 lm/W	Efficiency	100.00%
Source Flux	1231 lm	Maximum value	4326.59 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical


Round Luminaire	Diam. 55 mm	Height	130 mm
Round Luminous Area	Diam. 46 mm	Height	0 mm
Horizontal Luminous Area	0.001662 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.000402 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	22-10-2021	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	1231 lm

LED Flux=2254lm LED Power=21W Eff=55% EfcLed=107lm/W EfcLum=54lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(6K)=50000h

C.I.E.	100 100 100 100 100	D DIN 5040	A60
F UTE	--	B NBN	BZ 1



Diam=55mm



Semipiani C

180.0 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %

Luminaire
Code FU50201APP+AP91400
Name VECTOR 55 PENDANT FUNIVIA 927 WF BCO
Measurem.
Code FTS2001454-A
Name VECTOR 55 PENDANT FUNIVIA 927 WF BCO

Luminaire Flux	1231 lm	Luminaire Power	23.0 W	Efficacy	53.527 lm/W	Efficiency	100.00%
Source Flux	1231 lm	Maximum value	4326.59 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Round Luminaire	Diam. 55 mm	Height	130 mm
Round Luminous Area	Diam. 46 mm	Height	0 mm
Horizontal Luminous Area	0.001662 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.000402 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	22-10-2021	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	1231 lm

LED Flux=2254lm LED Power=21W Eff=55% EfcLed=107lm/W EfcLum=54lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(6K)=50000h


C.I.E.	100 100 100 100 100	D DIN 5040	A60
F UTE	--	B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.25	0.50	0.76	1.01	1.26	OC	0.25	0.50	0.76	1.01	1.26
OB	0.25	0.50	0.76	1.01	1.26	OD	0.25	0.50	0.76	1.01	1.26

Luminous Intensities [cd/klm]

	0	5	15	25	35	45	55	65	75	85
OA	5326.55	4887.31	2407.58	191.49	17.49	4.32	1.48	0.47	0.33	0.27
OB	5326.55	4887.31	2407.58	191.49	17.49	4.32	1.48	0.47	0.33	0.27
OC	5326.55	4887.31	2407.58	191.49	17.49	4.32	1.48	0.47	0.33	0.27
OD	5326.55	4887.31	2407.58	191.49	17.49	4.32	1.48	0.47	0.33	0.27



H[m]	D[m]	Max lux	Med lux	Alpha=14.1°+14.1°	G=0.0
1.00	0.50	5327	3305		
2.00	1.01	1332	826		
3.00	1.51	592	367		
4.00	2.01	333	207		
5.00	2.52	213	132		