

Luminaire


Code FU20004+AP91400
Name VECTOR 55 FUNIVIA 927 SP NRO

Measurement

Code FTS2001444-A
Name VECTOR 55 FUNIVIA 927 SP NRO

Luminaire Flux	954 lm	Luminaire Power	23.0 W	Efficacy	41.489 lm/W	Efficiency	100.00%
Source Flux	954 lm	Maximum value	9643.54 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	55 mm	Height	130 mm		
Round Luminous Area		Diam.	46 mm	Height	0 mm		
Horizontal Luminous Area		0.001662 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000402 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		19-10-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		954 lm	
LED Flux=2254lm LED Power=21W Eff=42% EfcLed=107lm/W EfcLum=41lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(6K)=50000h							
C.I.E.	100	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1


Diam=55mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %



Luminaire

Code FU20004+AP91400
Name VECTOR 55 FUNIVIA 927 SP NRO

Measurem.


Code FTS2001444-A
Name VECTOR 55 FUNIVIA 927 SP NRO

Luminaire Flux	954 lm	Luminaire Power	23.0 W	Efficacy	41.489 lm/W	Efficiency	100.00%
Source Flux	954 lm	Maximum value	9643.54 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	55 mm	Height	130 mm		
Round Luminous Area		Diam.	46 mm	Height	0 mm		
Horizontal Luminous Area		0.001662 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000402 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		19-10-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		954 lm	
LED Flux=2254lm LED Power=21W Eff=42% EfcLed=107lm/W EfcLum=41lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(6K)=50000h							
C.I.E.	100	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.14	0.27	0.41	0.54	0.68	OC	0.14	0.27	0.41	0.54	0.68
OB	0.14	0.27	0.41	0.54	0.68	OD	0.14	0.27	0.41	0.54	0.68

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	9202.25	7055.87	1081.25	135.63	13.21	3.77	1.34	0.43	0.34	0.26
OB	9202.25	7055.87	1081.25	135.63	13.21	3.77	1.34	0.43	0.34	0.26
OC	9202.25	7055.87	1081.25	135.63	13.21	3.77	1.34	0.43	0.34	0.26
OD	9202.25	7055.87	1081.25	135.63	13.21	3.77	1.34	0.43	0.34	0.26



H[m]	D[m]	Max lux	Med lux	Alpha=7.7°+7.7°	G=0.0
1.00	0.27	9202	5963		
2.00	0.54	2301	1491		
3.00	0.82	1022	663		
4.00	1.09	575	373		
5.00	1.36	368	239		