

Algoritmo System for projectors - Pre-Wired gear for PAD and PAD Square - Direct + indirect emission LED 3000K Non dimmable

Carlotta de Bevilacqua
Paola di Arianello



IP40 

LUMINAIRE

- Power Supply: **Electronic Integrated**
- Watt: **27W**
- Voltage: **220V-240V**
- Delivered lumen output: **2475lm**
- CCT: **3000K**
- Efficiency: **77%**
- Efficacy: **91.68lm/W**
- CRI: **80**

Notes

Allows intallation and supplying of 1 to 4 PAD 230V projectors. MV through-wiring included. Upper screen in PMMA included for double emission version. PAD projectors to be ordered separately.

DESCRIPTION

A modular system for ceiling or wall-recessed installation, to be installed as a continuous line or with angles, composed of structural modules in extruded aluminium, of pre-wired gear plates with through-wiring and quick-connection system of optics systems and components for connecting, fixing, joining or finishing the system. The prewired LED plates were designed for diffused emission, wall washer light, prismoptic or controlled emission, for projectors integration (PAD or Cube 37), for 3 phase track alimentation. Complies with standard EN60598-1 and any other specific standard.

FEATURES

- Product Code: **M2945W00**
- Installation: **Projector, Recessed, Ceiling**
- Series: **Architectural Indoor**
- design by: **Carlotta de Bevilacqua, Paola di Arianello**

DIMENSIONS

- Length: **1180 mm**
- Weight: **kg 1.2**
- Glow Wire Test: **650°**

Accessories

NO
IMAGE
AVAILABLE

Algoritmo System intermediate finishing connector (set of 2 pcs). To be used at the junction of modules with accent lighting and fluorescent or LED modules. Metal-grey paint finish. M217660

NO
IMAGE
AVAILABLE

ALGORTIMO - PAD for ALGORITMO - Blind panel. For closing the positions where no PAD projector is used. 1 piece required for each empty position. metal-grey M217760